

Specifications

Nominal Voltage	12V	
Nominal Capacity (20HR)	9AH	
Dimension	Length	151mm (5.95 inches)
	Width	65mm (2.56 inches)
	Height	94mm (3.70 inches)
	Total Height (with Terminal)	100mm (3.94 inches)
	Approximate Weight	2.65 kg (5.84 lbs)
Battery Type	Valve Regulated Lead-Acid Battery, AGM Design	
Terminal Type	NB	
Rated Capacity	9.00AH	(20hr, 1.75V/cell, 25°C/77°F)
	8.60AH	(10hr, 1.75V/cell, 25°C/77°F)
	7.65AH	(5hr, 1.75V/cell, 25°C/77°F)
	8.43AH	(3hr, 1.60V/cell, 25°C/77°F)
	5.99AH	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	130A	
Internal Resistance	18mΩ	
Operating Temp. Range	Discharge:	-20°C (-4°F)~50°C (122°F)
	Charge:	-20°C (-4°F)~50°C (122°F)
	Storage:	-20°C (-4°F)~40°C (104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Container Material	ABS (Option: 94-HB & 94-V0 flame retardant case)	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	SigmasTek HR series batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is recommended. For higher temperatures the time interval will be shorter.	



Applications

- Uninterruptible Power Supply (UPS)
- Electric wheelchairs, scooters, bikes
- Electronic apparatus and equipment
- Alarm and security systems
- Emergency first responder equipment
- Emergency lighting
- Medical devices
- Electric carts
- Telecom equipment
- Switchgear
- Solar power systems



Constant Current Discharge (Amperes Per Battery) at 25°C (77°F)

F.V. (V/cell) \ Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	35.5	25.4	18.5	10.5	5.99	3.25	2.81	1.66	1.06	0.92	0.51
1.67V	32.9	24.2	17.8	10.3	5.86	3.23	2.38	1.62	1.04	0.91	0.47
1.70V	30.4	23.6	17.4	10.1	5.80	3.22	2.25	1.58	1.03	0.88	0.46
1.75V	30.1	22.7	16.8	9.90	5.69	3.18	2.20	1.53	1.02	0.86	0.45
1.80V	26.6	21.7	16.2	9.66	5.60	3.12	2.14	1.51	1.00	0.85	0.45
1.85V	25.3	20.5	15.5	9.38	5.50	2.85	2.00	1.37	0.98	0.82	0.43




Constant Power Discharge (Watts Per Cell) at 25°C (77°F)

F.V. (V/cell) \ Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	72.0	47.7	35.2	20.7	11.9	6.50	4.58	3.67	2.07	1.77	0.92
1.67V	69.7	46.0	34.2	20.2	11.7	6.45	4.58	3.65	2.05	1.75	0.92
1.70V	66.7	45.0	33.7	20.0	11.7	6.43	4.57	3.63	2.05	1.73	0.90
1.75V	62.7	43.3	32.7	19.7	11.5	6.33	4.55	3.63	20.5	1.73	0.88
1.80V	54.5	41.7	31.8	19.3	11.3	6.25	4.52	3.62	2.03	1.70	0.87
1.85V	50.0	40.2	31.0	19.0	11.2	6.00	4.38	3.37	1.90	1.68	0.85


Dimensions

NB Terminal


Unit: mm (inches)




Cycle Service Life




Self Discharge Characteristics




Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Temperature Effects on Long Term Float Life



Contact Information

SigmatTek
7651 W 100th Place
Bridgeview, IL 60455, USA

T: (888) 988-8290
www.sigmastek.com
order@sigmastek.com