

Specifications

Nominal Voltage	12V	
Nominal Capacity (10HR)	65AH	
Dimension	Length	348mm (13.7 inches)
	Width	167mm (6.57 inches)
	Height	178mm (7.01 inches)
	Total Height (with Terminal)	178mm (7.01 inches)
	Approximate Weight	19.19 kg (42.3 lbs)
Battery Type	Valve Regulated Lead-Acid Battery, AGM Design	
Terminal Type	IT / NB	
Rated Capacity	65.8AH	(20hr, 1.75V/cell, 25°C/77°F)
	62.7AH	(10hr, 1.75V/cell, 25°C/77°F)
	53.6AH	(5hr, 1.75V/cell, 25°C/77°F)
	49.8AH	(3hr, 1.60V/cell, 25°C/77°F)
	37.5AH	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	780A	
Internal Resistance	7.3mΩ	
Operating Temp. Range	Discharge:	-20°C (-4°F)~50°C (122°F)
	Charge:	-20°C (-4°F)~50°C (122°F)
	Storage:	-20°C (-4°F)~40°C (104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Container Material	ABS (Option: 94-HB & 94-V0 flame retardant case)	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	SigmasTek SP series batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is recommended. For higher temperatures the time interval will be shorter.	



Applications

- Uninterruptible Power Supply (UPS)
- Electric wheelchairs, scooters, bikes
- Electronic apparatus and equipment
- Alarm and security systems
- Emergency first responder equipment
- Emergency lighting
- Medical devices
- Electric carts
- Telecom equipment
- Switchgear
- Solar power systems



Constant Current Discharge (Amperes Per Battery) at 25°C (77°F)

F.V. (V/cell) \ Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	210.1	138.2	109.3	65.0	37.5	22.1	16.6	11.38	7.83	6.48	3.38
1.65V	193.8	130.0	105.1	63.3	36.6	21.6	16.2	11.18	7.73	6.40	3.37
1.70V	177.1	120.7	100.1	61.4	35.6	21.1	15.8	10.97	7.62	6.33	3.32
1.75V	160.9	111.8	93.80	58.7	34.2	20.4	15.3	10.72	7.51	6.27	3.29
1.80V	142.7	102.5	85.90	55.7	32.7	19.7	14.9	10.47	7.40	6.21	3.25
1.85V	114.0	87.60	75.50	50.8	30.6	18.5	14.2	10.04	7.11	5.98	3.20





Constant Power Discharge (Watts Per Cell) at 25°C (77°F)

F.V. (V/cell) \ Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	348.4	235.0	191.2	118.4	70.5	41.9	31.6	21.9	15.30	12.74	6.66
1.65V	328.8	226.2	186.9	116.3	69.1	41.2	31.1	21.6	15.13	12.61	6.64
1.70V	304.9	211.9	179.5	113.6	67.7	40.4	30.4	21.3	14.94	12.49	6.56
1.75V	284.8	200.8	170.5	109.3	65.3	39.3	29.6	20.9	14.74	12.38	6.50
1.80V	258.1	187.0	158.1	104.6	62.8	37.9	29.0	20.4	14.56	12.27	6.43
1.85V	208.5	161.7	140.9	79.70	59.1	35.9	27.7	19.7	14.04	11.83	6.34


Dimensions

IT Terminal


Unit: mm (inches)




Cycle Service Life




Self Discharge Characteristics




Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Temperature Effects on Long Term Float Life



Contact Information

SigmatTek
7651 W 100th Place
Bridgeview, IL 60455, USA

T: (888) 988-8290
www.sigmastek.com
order@sigmastek.com