

Specifications

Nominal Voltage	2V	
Nominal Capacity (10HR)	800AH	
Dimension	Length	410mm (16.14 inches)
	Width	175mm (6.89 inches)
	Height	330mm (12.99 inches)
	Total Height (with Terminal)	350mm (13.78 inches)
Approximate Weight	51.5 kg (113.6 lbs)	
Battery Type	Valve Regulated Lead-Acid Battery, AGM Design	
Terminal Type	IT	
Rated Capacity	854.0AH	(20hr, 1.80V/cell, 25°C/77°F)
	800.0AH	(10hr, 1.80V/cell, 25°C/77°F)
	710.0AH	(5hr, 1.75V/cell, 25°C/77°F)
	617.7AH	(3hr, 1.75V/cell, 25°C/77°F)
	480.5AH	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	6400A	
Internal Resistance	0.5mΩ	
Operating Temp. Range	Discharge:	-15°C (5°F)~50°C (122°F)
	Charge:	0°C (32°F)~40°C (104°F)
	Storage:	-15°C (5°F)~40°C (104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Container Material	ABS (Option: 94-HB & 94-V0 flame retardant case)	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	SigmasTek SPL series batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is recommended. For higher temperatures the time interval will be shorter.	



Applications

- Tele - communication central station (wired or cellular)
- Military communication
- Data and television signal transmission
- UPS
- EPS



Constant Current Discharge (Amperes Per Battery) at 25°C (77°F)

F.V. (V/cell)	Discharge Time	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V		776.4	592.0	480.5	296.0	220.8	177.5	149.7	129.6	103.0	84.2	44.1
1.65V		750.7	576.5	469.5	290.4	217.1	175.0	147.5	127.8	101.5	83.0	43.8
1.70V		715.7	552.5	453.2	281.2	212.3	171.4	144.4	125.7	100.0	82.0	43.4
1.75V		682.1	532.4	437.8	270.4	205.9	167.7	142.0	123.5	98.30	81.0	42.9
1.80V		644.1	506.3	419.6	260.0	199.2	162.2	137.7	120.6	96.40	80.0	42.7
1.85V		600.3	481.3	401.3	248.8	189.9	155.2	132.2	115.5	92.40	77.0	41.2



Constant Power Discharge (Watts Per Cell) at 25°C (77°F)

F.V. (V/cell)	Discharge Time	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V		1423.2	1099.7	903.9	562.4	422.7	341.6	289.5	252.3	202.2	166.3	87.3
1.65V		1390.0	1081.0	889.2	555.2	417.7	338.4	286.5	249.7	199.7	164.2	86.8
1.70V		1335.1	1041.7	863.2	539.9	410.2	332.4	281.5	246.2	197.2	162.5	86.0
1.75V		1283.2	1011.0	838.4	521.4	399.4	326.7	277.5	242.3	194.0	160.7	85.1
1.80V		1221.0	967.10	807.1	503.3	387.5	317.0	270.2	237.4	190.7	158.9	84.8
1.85V		1147.2	925.40	776.2	483.9	371.1	304.5	260.4	228.2	183.4	153.2	82.1


Dimensions

IT Terminal


Unit: mm (inches)




Self Discharge Characteristics




Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Temperature Effects on Long Term Float Life



Contact Information

SigmasTek
7651 W 100th Place
Bridgeview, IL 60455, USA

T: (888) 988-8290
www.sigmastek.com
order@sigmastek.com