


Specifications

Nominal Voltage	12V	
Nominal Capacity (10HR)	150AH	
Dimension	Length	483mm (19.00 inches)
	Width	170mm (6.69 inches)
	Height	238mm (9.39 inches)
	Total Height (with Terminal)	238mm (9.39 inches)
Approximate Weight	43.5 kg (95.9 lbs)	
Battery Type	Valve Regulated Lead-Acid Battery, AGM Design	
Terminal Type	IT	
Rated Capacity	156AH	(20hr, 1.80V/cell, 25°C/77°F)
	150AH	(10hr, 1.80V/cell, 25°C/77°F)
	129AH	(5hr, 1.75V/cell, 25°C/77°F)
	117AH	(3hr, 1.75V/cell, 25°C/77°F)
	91.5AH	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	1500A	
Internal Resistance	3.5mΩ	
Operating Temp. Range	Discharge:	-20°C (-4°F)~50°C (122°F)
	Charge:	-20°C (-4°F)~50°C (122°F)
	Storage:	-20°C (-4°F)~40°C (104°F)
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Container Material	ABS (Option: 94-HB & 94-V0 flame retardant case)	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	SigmasTek SP series batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is recommended. For higher temperatures the time interval will be shorter.	



Applications

- Uninterruptible Power Supply (UPS)
- Electric wheelchairs, scooters, bikes
- Electronic apparatus and equipment
- Alarm and security systems
- Emergency first responder equipment
- Emergency lighting
- Medical devices
- Electric carts
- Telecom equipment
- Switchgear
- Solar power systems



Constant Current Discharge (Amperes Per Battery) at 25°C (77°F)

F.V. (V/cell)	Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	\		361.9	275.0	162.0	91.5	56.3	43.1	28.1	18.6	15.8	8.18
1.65V		471.8	333.3	257.2	153.5	88.4	54.5	41.8	27.2	18.4	15.6	8.13
1.70V		427.9	308.9	241.8	145.5	85.5	53.0	40.1	26.5	18.1	15.3	8.03
1.75V		388.5	283.4	226.5	139.8	82.9	51.0	39.0	25.8	17.9	15.1	7.88
1.80V		344.6	257.9	207.4	134.6	79.2	49.2	38.3	25.2	17.6	15.0	7.80
1.85V		256.7	201.8	171.6	114.1	70.7	45.0	35.6	23.5	16.6	14.2	7.73




Constant Power Discharge (Watts Per Cell) at 25°C (77°F)

F.V. (V/cell)	Discharge Time	5min	10min	15min	30min	1h	2h	3h	5h	8h	10h	20h
1.60V	\		615.1	481.2	295.4	172.0	106.9	82.3	54.2	36.3	31.0	16.1
1.65V		800.6	579.8	457.5	281.8	167.0	103.9	80.2	52.7	36.1	30.7	16.0
1.70V		736.5	542.2	433.6	269.3	162.7	101.7	77.3	51.4	35.6	30.2	15.8
1.75V		687.9	509.0	411.9	260.2	158.3	98.00	75.4	50.3	35.1	29.9	15.6
1.80V		623.4	470.8	381.8	252.7	152.0	94.80	74.3	49.1	34.6	29.6	15.4
1.85V		469.4	372.8	320.3	217.5	136.4	87.50	69.4	46.0	32.7	28.0	15.3


Dimensions

IT Terminal


Unit: mm (inches)




Cycle Service Life




Self Discharge Characteristics




Discharge Characteristics




Float Charging Characteristics



Temperature Effects in Relation to Battery Capacity



Temperature Effects on Long Term Float Life



Contact Information

SigmaTek
7651 W 100th Place
Bridgeview, IL 60455, USA

T: (888) 988-8290
www.sigmastek.com
order@sigmastek.com